



# Product data sheet

PURE 1 SPOT TRACK  
09.1005/QT-12/20W/35W/50W/57°  
FLOS




Luminaire for three-phase electric track installation. For very low voltage halogen lamps or standar and discharge lamps. Self-extinguishing ceramic or engineering plastic lamp holders, with single-pole, transparent electric wires with double teflon insulation.

## Light output 1




### 1 x Halogen low voltage lamp without reflector

|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 35 W    | Socket      | Gy6.35 |
| Lamp flux          | 600 lm  | LOR         | 63%    |
| Luminous efficacy  | 11 lm/W | Total flux  | 378 lm |
| CCT                | 3000 K  | Total power | 35 W   |
| CRI                | 99      |             |        |



### 1 x Halogen low voltage lamp without reflector

|                    |        |             |        |
|--------------------|--------|-------------|--------|
| Nominal lamp power | 20 W   | Socket      | E27    |
| Lamp flux          | 300 lm | LOR         | 63%    |
| Luminous efficacy  | 9 lm/W | Total flux  | 189 lm |
| CCT                | 2756 K | Total power | 22 W   |
| CRI                | 99     |             |        |



### 1 x Halogen low voltage lamp without reflector

|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 50 W    | Socket      | Gy6.35 |
| Lamp flux          | 910 lm  | LOR         | 63%    |
| Luminous efficacy  | 11 lm/W | Total flux  | 574 lm |
| CCT                | 3000 K  | Total power | 50 W   |
| CRI                | 99      |             |        |

## Mounting mode

Ceiling mounted

## Electric

System power: 22-50 W  
Appliance Class: I

#### Shape and measurements

Length: 1.69 in

Width: 4.34 in

Height: 5.31 in

#### Adjustability

Free

#### Protection

IP: 20