


# Product data sheet

LIGHT SNIPER SQUARE  
03.4601/QR-CBC 51/50W/10°24°36°60°  
FLOS




High performance luminaires for embedded installation for halogen lamps with dichroic reflector, metal halide reflector or LED lamps. They offer a high comfort due to the back visual position of light source. Body of the luminaire made of two bodies of injected aluminium. Square front ring made of steel sheet 1mm thick with white matt finish. It incorporates shielded cones made in zamak injection in three sets: black, matt gold and chrome. Fixed, tilt and wall-washers versions. Spreading lens made in opal tempered glass in halogen fixed and tilt versions. In wall-washer versions a distribution lens made of borosilicate is incorporated.

## Light output 1




### 1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gu5.3
Lamp flux	1012 lm	LOR	45%
Luminous efficacy	9 lm/W	Total flux	455 lm
CCT	3000 K	Total power	50 W
CRI	100		




### 1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gu5.3
Lamp flux	995 lm	LOR	63%
Luminous efficacy	13 lm/W	Total flux	630 lm
CCT	3000 K	Total power	50 W
CRI	100		



### 1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gu5.3
Lamp flux	1182 lm	LOR	64%
Luminous efficacy	15 lm/W	Total flux	757 lm
CCT	3000 K	Total power	50 W
CRI	100		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gu5.3
Lamp flux	1025 lm	LOR	65%
Luminous efficacy	13 lm/W	Total flux	668 lm
CCT	3000 K	Total power	50 W
CRI	100		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.94 in

Width: 3.94 in

Height: 5.91 in

Adjustability

Fixed

Electric

System power: 50 W

Appliance Class: II

Protection

IP: 44