


Product data sheet

RICHARD I (WALL FITTING)
9.841.1032.00
LEIPZIGER LEUCHTEN



Mounting height approx. 3.00 - 4.50 m, for medium light requirements. - Impact-resistant clear polycarbonate cylinder, UV-stablized - Mirror lamellae for light guidance and glare limitation made of premium highest-grade aluminium, burnished and anodized - Aluminium reflector finished in special white paint for max. light reflection - Aluminium cover painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components arranged on a block - Connection with adapter jack - Available in any RAL or DB colour without surcharge Wall luminaires Richard BI and BII as described above, except - Wall luminaire BI with opal cylinder, no mirror lamellae - Reflector made of impact-resistant RESIST plexiglas, inside finished in white paint, outside painted in colour Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x Metal halide lamp			
Nominal lamp power	70 W	LOR	59%
Lamp flux	7200 lm	ULOR	15%
Luminous efficacy	48 lm/W	Total flux	4260 lm
CCT	3000 K	Total power	89 W
CRI	90		

Mounting mode

Wall mounted

Shape and measurements

Height: 9.84 in
Diameter: 9.84 in

Electric

System power: 89 W

Protection

IP: 55
Designation labels: CE, ENEC, F