


Product data sheet

EVA II (W. SHIELD ON SIDE FACING BUILDING)
9.898.3042.25
LEIPZIGER LEUCHTEN



For high light requirements, mounting height 4.00 - 5.00 m. - Impact-resistant clear polycarbonate attachment, UV-stabilized - Large aluminium reflector for max. light output, inside in special white paint - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - Unit carrier made of hot die cast aluminium, corrosion-resistant, outside painted in colour - All electrical components are arranged on a block - Adapter jack for connection -Available in any RAL or DB colour without surcharge - Please order pole dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	48%
Lamp flux	4000 lm	ULOR	10%
Luminous efficacy	22 lm/W	Total flux	1925 lm
CCT	3400 K	Total power	89 W
CRI	54		

Mounting mode

Pole top mounted, Ceiling mounted

Shape and measurements

Height: 17.72 in
Diameter: 15.75 in

Design

Material impression: Matt
Color of housing: White

Electric

System power: 89 W
Ballast: ECG
Controller: DALI

Protection

IP: 55
Designation labels: CE, F

Other operating numbers

Ambient temperature range: -4...95°F