## Product data sheet

MARCEL II (WALL FITTING) 9.842.3046.00

LEIPZIGER LEUCHTEN









For medium and high light requirements, mounting height 3.80 m. - Impact-resistant clear polycarbonate attachment, UV-stabilized, - Reflector lamellae made of premium highest-grade aluminium, burnished and anodized for light guidance and glare limitation - Aluminium luminaire body, inside finished in white paint, outside painted in colour - Aluminium unit carrier, painted white - Adapter jack connection -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



1 x High pressure mercury vapour lamp		
Nominal lamp power	50 W	
Lamp flux	2000 lm	
Luminous efficacy	20 lm/W	
CCT	3400 K	
CRI	54	

LOR	60%
ULOR	10%
Total flux	1195 lm
Total power	59 W



i x High pressure mercury vapour lamp				
Nominal lamp power	80 W	LOR	60%	
Lamp flux	4000 lm	ULOR	10%	
Luminous efficacy	27 lm/W	Total flux	2390 lm	
CCT	3400 K	Total power	89 W	
CRI	54			

Mounting mode

Wall mounted

Shape and measurements

Height: 20.08 in Diameter: 20.08 in Electric

System power: 59-89 W

Protection

IP: 55