
Product data sheet

LUCAS IV (WALL FITTING BEADED) 9.834.2056.16 LEIPZIGER LEUCHTEN



Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet


Light output 1



1 y High pre	dium va	nour le	amn

IP 55

TX HIGH PRESSURE SOUIUN	i vapour iarrip		
Nominal lamp power	100 W	LOR	83%
Lamp flux	10400 lm	ULOR	2%
Luminous efficacy	75 lm/W	Total flux	8621 lm
CCT	2000 K	Total power	115 W
CRI	25		



1 x High pressure sodium va	anour lamn

51			
Nominal lamp power	70 W	LOR	83%
Lamp flux	5600 lm	ULOR	2%
Luminous efficacy	56 lm/W	Total flux	4642 lm
CCT	2000 K	Total power	83 W
CRI	25		

Mounting mode
Wall mounted
Shape and measurements

Height: 22.44 in Diameter: 22.44 in

Electric

System power: 83-115 W

Protection

IP: 55