

Product data sheet


RICHARD II (WALL FITTING)
9.844.3142.00
LEIPZIGER LEUCHTEN



IP
55


Mounting height approx. 3,00 - 4,50 m, for medium light requirements. - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Circular shield for glare limitation made of anodized aluminium - Large aluminium reflector, inside finished in special white paint for max. light reflection - Aluminium cover, painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components are arranged on a block - Connection with adapter jack -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp

| | | | |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 50 W | LOR | 43% |
| Lamp flux | 2000 lm | ULOR | 8% |
| Luminous efficacy | 15 lm/W | Total flux | 860 lm |
| CCT | 3400 K | Total power | 59 W |
| CRI | 54 | | |



1 x High pressure mercury vapour lamp

| | | | |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 80 W | LOR | 43% |
| Lamp flux | 4000 lm | ULOR | 8% |
| Luminous efficacy | 19 lm/W | Total flux | 1719 lm |
| CCT | 3400 K | Total power | 89 W |
| CRI | 54 | | |

Mounting mode

Wall mounted

Electric

System power: 59-89 W

Shape and measurements

Height: 9.84 in
Diameter: 9.84 in

Protection

IP: 55