


Product data sheet

PURE 3 DOWNLIGHT
09.1805/CDM-R1111/70W/10°24°40°
FLOS




Recessed luminaire for indoor application. For very low voltage halogen lamps or standard and discharge lamps. Self-extinguishing ceramic or engineering plastic lamp holders, with single-pole, transparent electric wires with double Teflon insulation.

Light output 1




1 x Metal halide lamp

Nominal lamp power	70 W	Socket	Gx12
Lamp flux	6600 lm	LOR	57%
Luminous efficacy	54 lm/W	Total flux	3747 lm
CCT	2900 K	Total power	70 W
CRI	84		



1 x Metal halide lamp

Nominal lamp power	70 W	Socket	Gx12
Lamp flux	6600 lm	LOR	45%
Luminous efficacy	42 lm/W	Total flux	2973 lm
CCT	2900 K	Total power	70 W
CRI	84		



1 x Metal halide lamp

Nominal lamp power	70 W	Socket	Gx12
Lamp flux	6600 lm	LOR	30%
Luminous efficacy	28 lm/W	Total flux	1978 lm
CCT	2900 K	Total power	70 W
CRI	84		

Mounting mode

Ceiling recessed

Electric

System power: 70 W
Appliance Class: I

Shape and measurements

Length: 5.91 in

Width: 5.91 in

Height: 5.51 in

Adjustability

Rotatable, Tilttable

Protection

IP: 20