


Product data sheet

SPOCK130 LED
541011
FLOS



• Adjustable LED luminaire for outdoor installation on ceiling, wall and ground. • Configuration: die-cast aluminium structure. EN AB 47100 alloy (low copper content) and AISI 316L stainless steel fixing bracket • Double layer coating for high resistance to corrosion: The low copper Aluminium alloy is painted with a double coat using powders which are complaint with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents).The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. • The luminaire has three connected parts: wiring unit (silicone gasket), heat sink and emitting unit (silicone glue). A graduated fixing plate allows a precise adjustment of the emitting unit. • Tempered transparent extra clear glass diffuser with silkscreen border. The glass is fixed through a robotic gluing system. • Protection Rating: IP66 • In compliance with EN60598-1 standards • Class of insulation: I • Installation: the luminaire is equipped with one M16 (Spock 75, 95) or M20 (Spock130) nickel plated brass cable gland and a piece of neoprene cable (approx. 1m) for an easy-to-make connection. • We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	52 W	CRI	80
Total flux	4003 lm	LOR	99%
Luminous efficacy	77 lm/W	Total power	52 W

Mounting mode

Wall mounted

Shape and measurements

Height: 5.12 in
Diameter: 5.12 in

Adjustability

Tiltable

Electric

System power: 52 W
Appliance Class: I

Protection

IP: 66
IK: 07