## Product data sheet

VOLKMAR I (1-ARMED) 9.870.0187.08

LEIPZIGER LEUCHTEN








For medium light requirements, mounting heights from 3.00 - 4.00 m. - Excellent uniform illumination, optimal glare protection - Luminaire body made of aluminium/galvanized steel sheet - Impact-resistant opal polyethylene attachment, UV-stabilized - Steel tubing galvanized and painted - Adapter jack connection -Available in any RAL or DB colour without surcharge -Order pole for single-bracket luminaire, dia. 60 mm, separately -Order pole for multi-bracket luminaire, dia. 76 mm,separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated


## Light output 1



1 x High pressure sodium vap	oour lamp
Nominal lamp power	50 V
Loppe flux	2500 lp

Lamp flux3500 lmLuminous efficacy41 lm/WCCT2000 KCRI25

LOR 73%
ULOR 28%
Total flux 2545 lm
Total power 62 W



## 1 x High pressure sodium vapour lamp

Nominal lamp power 70 W
Lamp flux 5600 lm
Luminous efficacy 49 lm/W
CCT 2000 K
CRI 25

LOR 73%
ULOR 28%
Total flux 4072 lm
Total power 83 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 28.35 in Diameter: 16.14 in Electric

System power: 62-83 W

Protection

IP: 55