
## Product data sheet

VOLKMAR II (WALL FITTING) 9.840.0080.05



For medium light requirements, mounting heights from 3.00 - 4.00 m. - Luminaire body made of aluminium/galvanized steel sheet - Impactresistant clear polycarbonate attachment, UV-stabilized - Steel tubing galvanized and painted - Adapter jack connection -Available in any RAL or DB -colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



$\times$	F	T	$\sim \times$
$\wedge$	XH	-77-	$\sim$
54 A	XH	7-0	$\sim$
LT	XXII	IXX	47
Tr	47 CU	1000	
		LTT.	
Ht	XA	XX >	TH
74	XH	$+\times$	24
$\langle \vee \rangle$	XI	IX	$\times/7$
$\sim$	$\sim$	-1-1	$\sim$

1 x High pressure mercury v	apour lamp
NET STATE TO A STATE STATE	10514

IP 55

Nominal lamp power	125 W	LOR	85%
Lamp flux	6800 lm	ULOR	28%
Luminous efficacy	42 lm/W	Total flux	5755 lm
CCT	3400 K	Total power	137 W
CRI	54		

1 x High pressure mercury vapour lamp						
Nominal lamp power	80 W	LOR	85%			
Lamp flux	4000 lm	ULOR	28%			
Luminous efficacy	38 lm/W	Total flux	3385 lm			
CCT	3400 K	Total power	89 W			
CRI	54					

Wall mounted

## Shape and measurements

Height: 16.14 in Diameter: 16.14 in Electric System power: 89-137 W Protection

IP: 55