Product data sheet

PAULA VII 9.647.2152.05

LEIPZIGER LEUCHTEN








Recommended mounting height 4.50 - 6.00 m, other heigts please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack - Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1




1 x High pressure sodium vapour lamp	
Nominal lamp power	50 W
Lamp flux	3500 lm
Luminous efficacy	47 lm/W

 Luminous efficacy
 47 lm/W

 CCT
 2000 K

 CRI
 25

1 x High pressure sodium vapour lamp



i x High pressure sodium vapour lamp	
Nominal lamp power	70 W
Lamp flux	5600 lm
Luminous efficacy	56 lm/W
CCT	2000 K
CRI	25

LOR 83%
Total flux 4654 lm
Total power 83 W

83%

2909 lm

62 W

LOR

Total flux

Total power

Mounting mode

Pole top mounted

Shape and measurements

Height: 28.74 in Diameter: 28.74 in

Design

Material impression: Matt Color of housing: Black Electric

System power: 62-83 W

Ballast: ECG

Protection

IP: 55

Designation labels: CE

Other operating numbers

Ambient temperature range: 14...95°F