

Product data sheet


CLARA IV/R U LED (SYMMETRICAL)
9.764.9022.05-24
LEIPZIGER LEUCHTEN



IP
65

recom. pole height: 3.00m – 5.00m light standards: for low and medium lighting requirements lamp: incl. 1 glare-free U LED-module colour temperature: 3.000K warm white or 4.000K neutral white LED gear: electronic driver, up to 50.000 hours, high efficiency factor of 94%, with soft start function and Constant Light Output (CLO) in order to keep the luminous flux the same over the entire life time LED life expectancy: up to 50.000 hours/ L100 for minimum maintenance costs due to an excellent thermal management light control: at extra cost: power reduction or dimming or CLEVER LIGHT or external change of dim settings subsequently optical system: louvre system with inner laying satined anti-glare tube and directed LEDs for wide spacings light distribution: symmetrical or asymmetrical luminaire head: canopy made of aluminium with a special white, reflective underside finish, base made of corrosion- resistant cast aluminium, powder coated glazing: PMMA RESIST, clear, high-impact colour: RAL or DB wiring: via a plug and socket connector outside the luminaire head; easy installation installation: for top entry ø 76mm; delivery in one piece accessories: cable, adapter AD 150 for concrete poles, column, pole accessories - to be ordered separately application areas: residential and local distributor roads, car parks, schools, hotels, factory premises, paths, squares, parks

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	13 W	CRI	80
Total flux	1533 lm	LOR	100%
Luminous efficacy	118 lm/W	ULOR	17%
		Total power	13 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 21.85 in

Diameter: 29.53 in

Adjustability

Height adjustable

Electric

System power: 13 W

Protection

IP: 65