Product data sheet

LUCAS VII (1-ARMED) 9.857.2056.15

LEIPZIGER LEUCHTEN









High-quality mirror optics provide good glare protection and enable mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with fork-type painted special steel brackets -Available in any RAL or DB colour without surcharge - Pole: dia. 76 mm, please order separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure sodium vapour lamp		
Nominal lamp power	100 W	
Lamp flux	10400 lm	
Luminous efficacy	72 lm/W	
CCT	2000 K	
CRI	25	

LOR	80%
ULOR	4%
Total flux	8284 lm
Total power	115 W



1 x High pressure sodium vapour lamp				
Nominal lamp power	70 W	LOR	80%	
Lamp flux	5600 lm	ULOR	4%	
Luminous efficacy	54 lm/W	Total flux	4461 lm	
CCT	2000 K	Total power	83 W	
CBI	25			

Mounting mode

Pole top mounted

Shape and measurements

Height: 23.62 in Diameter: 22.44 in Electric

System power: 83-115 W

Protection

IP: 55