Product data sheet

LUCAS I (WALL FITTING BEADED) 9.835.3162.16 LEIPZIGER LEUCHTEN




Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets -

IP 55

Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp					
Nominal lamp power	125 W	LOR	83%		
Lamp flux	6800 lm	ULOR	2%		
Luminous efficacy	41 lm/W	Total flux	5637 lm		
ССТ	3400 K	Total power	137 W		
CRI	54				

T + 737	"AFT
\otimes	
\sum	TY

1 x High pressure mercury vapour lamp					
5 1			0.004		
Nominal lamp power	80 W	LOR	83%		
Lamp flux	4000 lm	ULOR	2%		
Luminous efficacy	37 lm/W	Total flux	3316 lm		
CCT	3400 K	Total power	89 W		
CRI	54				

punting mode	Electric
all mounted	System power: 89-137 W
ape and measurements	Protection
ight: 22.44 in	IP: 55

Мо Wa

Sha

Hei Diameter: 22.44 in