

# Product data sheet

VOLKMAR II (3-ARMED)

9.870.0197.05


LEIPZIGER LEUCHTEN



IP  
55

For medium light requirements, mounting heights from 3.00 - 4.00 m. - Luminaire body made of aluminium/galvanized steel sheet - Impact-resistant clear polycarbonate attachment, UV-stabilized - Steel tubing galvanized and painted - Adapter jack connection - Available in any RAL - or DB -colour without surcharge -Order pole for single-bracket luminaire, dia. 60 mm, separately -Order pole for multi-bracket luminaire, dia. 76 mm, separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

## Light output 1




### 1 x High pressure sodium vapour lamp

|                    |         |
|--------------------|---------|
| Nominal lamp power | 70 W    |
| Lamp flux          | 5600 lm |
| Luminous efficacy  | 57 lm/W |
| CCT                | 2000 K  |
| CRI                | 25      |

|             |         |
|-------------|---------|
| LOR         | 85%     |
| ULOR        | 28%     |
| Total flux  | 4739 lm |
| Total power | 83 W    |

## Light output 2




### 1 x High pressure sodium vapour lamp

|                    |         |
|--------------------|---------|
| Nominal lamp power | 70 W    |
| Lamp flux          | 5600 lm |
| Luminous efficacy  | 57 lm/W |
| CCT                | 2000 K  |
| CRI                | 25      |

|             |         |
|-------------|---------|
| LOR         | 85%     |
| ULOR        | 28%     |
| Total flux  | 4739 lm |
| Total power | 83 W    |

## Light output 3



### 1 x High pressure sodium vapour lamp

|                    |         |
|--------------------|---------|
| Nominal lamp power | 70 W    |
| Lamp flux          | 5600 lm |
| Luminous efficacy  | 57 lm/W |
| CCT                | 2000 K  |
| CRI                | 25      |

|             |         |
|-------------|---------|
| LOR         | 85%     |
| ULOR        | 28%     |
| Total flux  | 4739 lm |
| Total power | 83 W    |

**Mounting mode**

Pole top mounted

**Shape and measurements**

Height: 28.35 in

Diameter: 16.14 in

**Electric**

System power: 249 W

**Protection**

IP: 55