


Product data sheet

NEW TORCIA
528006
FLOS



Outdoor cylindrical bollard light. Double layer coating for high resistance to corrosion: The aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Transparent polycarbonate diffuser with metal antiglare louvre for fluorescent versions.

Light output 1



1 x Compact fluorescent lamp			
Nominal lamp power	18 W	Socket	G24D-2
Lamp flux	1200 lm	LOR	42%
Luminous efficacy	28 lm/W	ULOR	24%
CCT	3000 K	Total flux	509 lm
CRI	84	Total power	18 W

Mounting mode

Pole top mounted, Standing / Bollard

Shape and measurements

Height: 9.06 in
Diameter: 3.15 in

Adjustability

Fixed

Electric

System power: 18 W
Appliance Class: I

Protection

IP: 65
IK: 09