

Product data sheet


NADJA IV (1-ARMED)
9.879.2036.05
LEIPZIGER LEUCHTEN



IP
55

Recommended mounting height 3.50 - 5.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711
Luminaires generally compensatet


Light output 1



1 x High pressure sodium vapour lamp

| | |
|--------------------|---------|
| Nominal lamp power | 50 W |
| Lamp flux | 3500 lm |
| Luminous efficacy | 44 lm/W |
| CCT | 2000 K |
| CRI | 25 |

| | |
|-------------|---------|
| LOR | 78% |
| Total flux | 2737 lm |
| Total power | 62 W |



1 x High pressure sodium vapour lamp

| | |
|--------------------|---------|
| Nominal lamp power | 70 W |
| Lamp flux | 5600 lm |
| Luminous efficacy | 53 lm/W |
| CCT | 2000 K |
| CRI | 25 |

| | |
|-------------|---------|
| LOR | 78% |
| Total flux | 4379 lm |
| Total power | 83 W |

Mounting mode

Pole top mounted

Shape and measurements

Height: 16.54 in

Diameter: 16.54 in

Electric

System power: 62-83 W

Protection

IP: 55