


Product data sheet

PURE 1 SPOT PRO CEILING
09.1170/QR-CBC 51/50W/10°/24°/36°/60°
FLOS




Luminaire for ceiling or three-phase electric track installation. For very low voltage halogen lamps or standar and discharge lamps. Self-extinguishing ceramic or engineering plastic lamp holders, with single-pole, transparent electric wires with double teflon insulation.

Light output 1




1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gu5.3
Lamp flux	1012 lm	LOR	38%
Luminous efficacy	8 lm/W	Total flux	389 lm
CCT	3000 K	Total power	50 W
CRI	100		




1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gu5.3
Lamp flux	995 lm	LOR	28%
Luminous efficacy	6 lm/W	Total flux	282 lm
CCT	3000 K	Total power	50 W
CRI	100		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gu5.3
Lamp flux	1182 lm	LOR	52%
Luminous efficacy	12 lm/W	Total flux	610 lm
CCT	3000 K	Total power	50 W
CRI	100		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gu5.3
Lamp flux	1025 lm	LOR	46%
Luminous efficacy	9 lm/W	Total flux	471 lm
CCT	3000 K	Total power	50 W
CRI	100		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 1.69 in
Width: 4.34 in
Height: 5.31 in

Adjustability

Free

Electric

System power: 50 W
Appliance Class: I

Protection

IP: 20