

Product data sheet


OKHOLM TUBE STORRUMSPENDEL T5 3X14/24W DALI
113706
DEFA LIGHTING



IP
20


Storrumsspendel i Opal acrylrør. Finnes for 3x14/24-21/39-28/54-35/49 Lengder på 625/925/1225 og 1449mm. Ø=200mm Med og uten DALI dim. Andre utførelser på forespørsel

Light output 1




3 x Fluorescent lamp tubular T5

Nominal lamp power	24 W	Socket	G5
Lamp flux	1750 lm	LOR	71%
Luminous efficacy	48 lm/W	ULOR	35%
CCT	4000 K	Total flux	3750 lm
CRI	85	Total power	78 W




3 x Fluorescent lamp tubular T5

Nominal lamp power	24 W	Socket	G5
Lamp flux	1750 lm	LOR	71%
Luminous efficacy	48 lm/W	ULOR	35%
CCT	3000 K	Total flux	3750 lm
CRI	85	Total power	78 W



3 x Fluorescent lamp tubular T5

Nominal lamp power	16 W	Socket	G5
Lamp flux	1200 lm	LOR	71%
Luminous efficacy	33 lm/W	ULOR	35%
CCT	4000 K	Total flux	2572 lm
CRI	85	Total power	78 W



3 x Fluorescent lamp tubular T5

Nominal lamp power	16 W	Socket	G5
Lamp flux	1200 lm	LOR	71%
Luminous efficacy	33 lm/W	ULOR	35%
CCT	3000 K	Total flux	2572 lm
CRI	85	Total power	78 W

Mounting mode

Pendant

Shape and measurements

Height: 24.61 in
Diameter: 7.87 in

Adjustability

Fixed

Electric

System power: 78 W

Protection

IP: 20