


Product data sheet

PURE 3 SPOT TRACK
09.1918/QR-111/100W/8°24°40°
FLOS




Luminaire for three-phase electric track installation. For very low voltage halogen lamps or standar and discharge lamps. Self-extinguishing ceramic or engineering plastic lamp holders, with single-pole, transparent electric wires with double teflon insulation.

Light output 1




1 x Halogen low voltage lamp without reflector

Nominal lamp power	100 W	Socket	G5.3
Lamp flux	1089 lm	LOR	100%
Luminous efficacy	11 lm/W	Total flux	1089 lm
CCT	3000 K	Total power	100 W
CRI	99		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	100 W	Socket	G5.3
Lamp flux	1368 lm	LOR	100%
Luminous efficacy	14 lm/W	Total flux	1369 lm
CCT	3000 K	Total power	100 W
CRI	99		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	100 W	Socket	G5.3
Lamp flux	977 lm	LOR	101%
Luminous efficacy	10 lm/W	Total flux	983 lm
CCT	3000 K	Total power	100 W
CRI	99		

Mounting mode

Ceiling mounted

Electric

System power: 100 W
Appliance Class: I

Shape and measurements

Length: 1.69 in

Width: 5.63 in

Height: 6.22 in

Adjustability

Free

Protection

IP: 20