


# Product data sheet

FRANCO  
961414  
FLOS



Outdoor luminaire for installation on wall or on pole. Configuration: die-cast aluminium structure. EN AB-47100 (low copper content) Double layer coating for high resistance to corrosion: The low copper Aluminium alloy is painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. The luminaire is equipped with a graduated stainless steel fixing plate allowing a precise installation on the wall.

## Light output 1



### 1 x Halogen low voltage lamp without reflector

Nominal lamp power	200 W	Socket	R7S
Lamp flux	3520 lm	LOR	57%
Luminous efficacy	10 lm/W	Total flux	2017 lm
CCT	2900 K	Total power	200 W
CRI	100		

## Mounting mode

Wall mounted

## Shape and measurements

Length: 9.65 in

Width: 5.04 in

Height: 12.87 in

## Adjustability

Tiltable

## Electric

System power: 200 W

Appliance Class: I

## Protection

IP: 65

IK: 07