


Product data sheet

ZEFIRO LED
532007
FLOS



• Outdoor cylindrical bollard light. • Configuration: die-cast aluminium cap EN AB-47100 alloy (low copper content) and extruded aluminium pole • Double layer coating for high resistance to corrosion: The aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents).The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. • Transparent UV-stabilised polycarbonate diffuser, silicone gaskets

Light output 1 (integrated)



Lamp type	LED	CCT	6000 K
Nominal lamp power	17 W	CRI	70
Total flux	1398 lm	LOR	100%
Luminous efficacy	82 lm/W	ULOR	25%
		Total power	17 W

Mounting mode

Standing / Bollard

Shape and measurements

Height: 39.37 in
Diameter: 5.91 in

Adjustability

Fixed

Electric

System power: 17 W
Appliance Class: II

Protection

IP: 65
IK: 07