
## Product data sheet

LUCAS VIII (1-ARMED BEADED) 9.858.1072.16

LEIPZIGER LEUCHTEN








High-quality mirror optics provide good glare protection and enable mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets -Available in any RAL or DB colour without surcharge - Pole for single-bracket luminaire: dia. 76 mm, please order separately, inquire separately for pole to suit double-bracket luminaire Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



| 1 x Metal halide lamp |
|-----------------------|
| Nominal lamp power    |
| Lamp flux             |
| Luminous efficacy     |
| CCT                   |
| CRI                   |

| 150 W    |
|----------|
| 15000 lm |
| 71 lm/W  |
| 2900 K   |
| 90       |
|          |

| LOR         | 80%      |
|-------------|----------|
| ULOR        | 4%       |
| Total flux  | 11998 lm |
| Total power | 170 W    |
|             |          |

Mounting mode

Pole top mounted

Shape and measurements

Height: 23.62 in Diameter: 22.44 in Electric

System power: 170 W

Protection

IP: 55