


# Product data sheet

MINISILVIA ON POST  
935979  
FLOS



• Outdoor luminaire for installation on wall, ceiling and floor. The version “on post” is only for installation on floor. • Configuration: die-cast aluminium structure EN AB-47100 alloy (low copper content), extruded aluminium pole (version “on post”), borosilicate transparent or sandblasted glass, moulded silicone gaskets. Double layer coating for high resistance to corrosion: The aluminium components are painted with a double coat using powders which are complaint with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting.

## Light output 1



### 1 x Compact fluorescent lamp

Nominal lamp power	18 W	Socket	G24Q-2
Lamp flux	1200 lm	LOR	19%
Luminous efficacy	13 lm/W	ULOR	6%
CCT	3000 K	Total flux	229 lm
CRI	84	Total power	18 W

## Mounting mode

Standing / Bollard

## Shape and measurements

Height: 37.40 in  
Diameter: 7.09 in

## Adjustability

Fixed

## Electric

System power: 18 W  
Appliance Class: I

## Protection

IP: 65  
IK: 07