

# Product data sheet

CLARA I (WITH SHIELD ON SIDE FACING BUILDING, CLEAR ATTACHMENT)


9.761.1052.25

LEIPZIGER LEUCHTEN



For medium/high light requirements, mounting height 4.00 – 7.00 m. - Impact-resistant clear/opal polycarbonate attachment,UV- stabilized - High-pressure lamps with coated bulbs use reflector lamellae made of premium highest-grade aluminium, burnishid and anodized, for light guidance and glare limitation - Computer-optimized reflector system for high-pressure lamps with clear glass tubular bulbs ensures excellent illumination - Aluminium reflector finished in special white paint for max. light reflection - Corrosion-resistant cast aluminium unit carrier, painted - All electrical components on one block - Adapter jack connection -Available in any RAL or DB colour without surcharge - for post dia. 76 mm; order post dia.76 mm separately

## Light output 1



### 1 x Metal halide lamp

Nominal lamp power	100 W	LOR	50%
Lamp flux	10000 lm	ULOR	8%
Luminous efficacy	44 lm/W	Total flux	5044 lm
CCT	3000 K	Total power	115 W
CRI	90		

## Mounting mode

Pole top mounted

## Electric

System power: 115 W

## Shape and measurements

Height: 35.43 in

Diameter: 29.92 in