


Product data sheet

THETA LED
519001 NARROW BEAM
FLOS



• Spotlight for outdoor installation on wall, ceiling or floor. • Configuration: turned aluminium body (EN AW 6060). 316L stainless steel fixing bracket and methacrylate lens. Double layer coating for high resistance to corrosion: The aluminium components are painted with a double coat using powders which are complaint with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents).The entire painting process of the aluminium fitting starts from components which have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. • Stainless steel cable gland.

Light output 1 (integrated)



Lamp type	LED	CCT	6000 K
Nominal lamp power	3.4 W	CRI	70
Total flux	71 lm	LOR	100%
Luminous efficacy	21 lm/W	Total power	3.4 W

Mounting mode

Wall mounted

Shape and measurements

Height: 1.69 in
Diameter: 1.69 in

Adjustability

Tiltable

Electric

System power: 3.4 W
Appliance Class: III

Protection

IP: 65
IK: 04