

# Product data sheet


DIETER II (1-ARMED W. SHIELD ON SIDE FACING BUILDING)  
9.894.5497.25  
LEIPZIGER LEUCHTEN



IP  
65

Recommended mounting height 4.00 - 5.00 m. - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Special steel frame, painted - Large aluminium reflector, underside finished in special white paint for max. light reflection - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - All electrical components on one block - Adapter jack connection - Lamps are easy to change - Available in any RAL or DB color without surcharge - Please order pole mount dia. 76 mm separately  
Voltage: 230V 50Hz Protected to: IP 65 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

## Light output 1



### 1 x Compact fluorescent lamp

Nominal lamp power	26 W	LOR	50%
Lamp flux	1800 lm	ULOR	18%
Luminous efficacy	32 lm/W	Total flux	899 lm
CCT	2899 K	Total power	28 W
CRI	90		

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 19.69 in

Diameter: 10.63 in

## Electric

System power: 28 W

## Protection

IP: 65