


# Product data sheet

ALPHABET FOCUS RECESSED LUMINAIRE, FULLY RECESSED ADJUSTABLE SPOTLIGHT  
AF2103001-33-30\_(ALPHA-MIN)  
SCHMITZ | WILA



alphabet focus LED 3000 K Recessed Luminaire, Light distribution direct Fully Recessed Adjustable Spotlight Product: AF2103001-33-30  
Operating technology: independent driver required Light Technique highly precise lens technology (PLT) for beam angles, with focus unit for stepless fine adjustment Light module 361° rotatable, with integrated rotation stop tilt range from 0-30° variable beam angles 14° - 24° CRI > 90 constant colour temperature 3000 K lifetime 50.000 h (L70) Aluminium reflector (Al99.98), high- polished Luminaire housing stable housing design, made of aluminium die-cast and UV resistant plastics minimised ring thickness of only 2 mm for homogeneous appearance in the ceiling cover frame white, RAL 9016 Operating and assembly technology LED driver to be ordered separately Driver suitable for connection to central battery systems Quick installation due to 4-point screw fixing Suitable for ceiling thicknesses of 12-25 mm (1-12 mm by using optional extension kit, Art.-No. 89081) Reflector with safety suspension Lamp Wattage: 18 W Colour Rendering Index: 90 Colour Temperature: 3000 K Luminaire Luminous Flux: 340 Llm - 710 Llm System Efficiency: 36 Llm/W Half-peak Divergence α: 14° - 24° Number Luminaires LZ: 0.34 - 0.16 Connector: Screw Connector, 3 x 1.5 mm<sup>2</sup> Reflector Size: Q10 Length: 127 mm Width: 127 mm Cut-out length: 120 mm Cut-out width: 120 mm Overhang OH: 115 mm Installation Depth RD: 200 mm Total Weight: 1.1 kg Degree of Protection IP20 CE-Sign Total system: Protection class 2 Data record AF2103001-33-30\_(Alpha-MIN)

## Light output 1



### 1 x General service incandescent lamp

Nominal lamp power	20 W	LOR	100%
Lamp flux	340 lm	Total flux	340 lm
Luminous efficacy	17 lm/W	Total power	20 W
CCT	3000 K		
CRI	90		

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 5.00 in  
Width: 5.00 in  
Height: 7.87 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 20 W  
Appliance Class: II

## Protection

IP: 20