


Product data sheet

VARIUS 2
LED-LAMP
BRIGHT SPECIAL LIGHTING



The luminaire VARIUS 2 is appropriate for placement in exterior areas. It is made from castpressed aluminium (body and cover) by electrostatic and polyester dye. It dispose mirror with asymmetric beam made by clean aluminium 99,9% anodized. The lighting design of the mirror & cover achieve the asymmetric lighting beam and the avoidance of glare. Its waterproof is achieved by four (4) stainless allen screws, silicon rubber of high resistance and a fire resistant glass of 3mm thickness protection. The degree of protection from dust and dampness is IP65. The biggest temperature on the surface of the luminaire is 45oC. Operation in 230V/50Hz, while, for the use of compact fluorescent lamps is used built-in full electro mechanic control gear.

Light output 1



1 x LED			
Nominal lamp power	6.5 W	LOR	26%
Lamp flux	832 lm	Total flux	218 lm
Luminous efficacy	128 lm/W	Total power	18 W
CCT	3114 K		
CRI	83		

Mounting mode

Wall mounted

Shape and measurements

Length: 7.87 in
Width: 7.09 in
Height: 2.76 in

Adjustability

Fixed

Electric

System power: 18 W
Appliance Class: I

Protection

IP: 65
IK: 10