## Product data sheet

LUCAS VIII (1-ARMED) 9.858.2052.15

LEIPZIGER LEUCHTEN








High-quality mirror optics provide good glare protection and enable mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets -Available in any RAL or DB colour without surcharge - Pole for single-bracket luminaire: dia. 76 mm, please order separately, inquire separately for pole to suit double-bracket luminaire Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



I x High pressure sodium	vapour lamp
Nominal lamp power	100 W
Lamp flux	10400 lm
Luminous efficacy	72 lm/W

CCT 2000 K
CRI 25

LOR 80%
ULOR 4%
Total flux 8284 lm
Total power 115 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 23.62 in Diameter: 22.44 in Electric

System power: 115 W

Protection

IP: 55