


# Product data sheet

NORA I (1-ARMED)  
9.771.5521.05  
LEIPZIGER LEUCHTEN



For medium light requirements, mounting height 3.50 - 4.00 m. - Impact-resistant clear or beaded polycarbonate attachment, UV-stabilized - Special reflector of premium highest-grade aluminium, burnished and anodized, for excellent illumination and glare protection -Aluminium luminaire body, inside finished in white paint, outside painted in colour - Aluminium unit carrier, painted white - Adapter jack connection - Available in any RAL or DB colour without surcharge - Scope of delivery includes special steel post/wall-mounted bracket, painted -Order post dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



1 x Compact fluorescent lamp			
Nominal lamp power	23 W	LOR	76%
Lamp flux	1500 lm	ULOR	2%
Luminous efficacy	50 lm/W	Total flux	1143 lm
CCT	2571 K	Total power	23 W
CRI	90		

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 11.81 in  
Diameter: 21.26 in

## Electric

System power: 23 W

## Protection

IP: 55  
Designation labels: CE, ENEC, F