## Product data sheet

LUCAS II (1-ARMED BEADED) 9.852.2036.16

LEIPZIGER LEUCHTEN









Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge - Pole for single-bracket luminaire: dia. 76 mm, please order separately inquire separately for pole to suit double-bracket luminaire, Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



1 x High pressure sodium vapour lamp					
Nominal lamp power	50 W	LOR			
Lamp flux	3500 lm	ULOR			
Luminous efficacy	47 lm/W	Total flux			
CCT	2000 K	Total power			
CRI	25				

LOB 83%
LOTT
ULOR 2%
Total flux 2901 lm
Total power 62 W



1 x High pressure sodium vapour lamp				
Nominal lamp power	70 W	LOR	83%	
Lamp flux	5600 lm	ULOR	2%	
Luminous efficacy	56 lm/W	Total flux	4642 lm	
CCT	2000 K	Total power	83 W	
CRI	25			

Mounting mode

Pole top mounted

Shape and measurements

Height: 19.69 in Diameter: 22.44 in Electric

System power: 62-83 W

Protection

IP: 55