## Product data sheet

DIETER II (WALL FITTING) 9.839.2056.05

LEIPZIGER LEUCHTEN









Recommended mounting height 4.00 - 5.00 m. - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Special steel frame, painted -Large aluminium reflector, underside finished in special white paint for max. light reflection - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - All electrical components on one block - Adapter jack connection - Lamps are easy to change -Available in any RAL or DB color without surcharge Voltage: 230V 50Hz Protected to: IP 65 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

## Light output 1



1 x High pressure sodium vapour lamp				
Nominal lamp power	100 W			
Lamp flux	10400 lm			
Luminous efficacy	47 lm/W			
CCT	2000 K			
CRI	25			

LOR	52%
ULOR	13%
Total flux	5382 lm
Total power	115 W



1	хŀ	ligh	1	pressure	sodium	vapour	lamp
			ï				

5 1			
Nominal lamp power	70 W	LOR	52%
Lamp flux	5600 lm	ULOR	13%
Luminous efficacy	35 lm/W	Total flux	2898 lm
CCT	2000 K	Total power	83 W
CRI	25		

Mounting mode

Wall mounted

Shape and measurements

Height: 10.63 in Diameter: 10.63 in Electric

System power: 83-115 W

Protection

IP: 65