

Product data sheet

PAULA I (BEADED)
9.641.2032.06
LEIPZIGER LEUCHTEN



Recommended mounting height 4.50 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - all designs to suit non-glare class KB 1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack - Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure sodium vapour lamp

Nominal lamp power	70 W	LOR	86%
Lamp flux	5600 lm	Total flux	4828 lm
Luminous efficacy	58 lm/W	Total power	83 W
CCT	2000 K		
CRI	25		

Mounting mode

Pole top mounted

Shape and measurements

Height: 28.74 in
Diameter: 28.74 in

Electric

System power: 83 W

Protection

IP: 55