

Product data sheet

RICHARD II (2-ARMED)
9.893.5547.00
LEIPZIGER LEUCHTEN



IP
55

Mounting height approx. 3,00 - 4,50 m, for medium light requirements. - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Circular shield for glare limitation made of anodized aluminium - Large aluminium reflector, inside finished in special white paint for max. light reflection - Aluminium cover, painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components are arranged on a block - Connection with adapter jack -Available in any RAL or DB colour without surcharge -Order pole, dia. 60 mm, separately Order pole for double-bracket luminaire, dia. 76 mm, separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet


Light output 1



1 x Compact fluorescent lamp

Nominal lamp power	42 W	LOR	43%
Lamp flux	3200 lm	ULOR	8%
Luminous efficacy	30 lm/W	Total flux	1375 lm
CCT	2899 K	Total power	46 W
CRI	90		

Light output 2



1 x Compact fluorescent lamp

Nominal lamp power	42 W	LOR	43%
Lamp flux	3200 lm	ULOR	8%
Luminous efficacy	30 lm/W	Total flux	1375 lm
CCT	2899 K	Total power	46 W
CRI	90		

Mounting mode

Pole top mounted

Electric

System power: 92 W

Shape and measurements

Height: 24.21 in

Diameter: 9.84 in

Protection

IP: 55