Product data sheet

NADJA I (WALL FITTING) 9.840.3162.05

LEIPZIGER LEUCHTEN









Recommended mounting height 4.00 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury	vapour lamp
Nominal lamp power	125 W
Lamp flux	6800 lm
Luminous efficacy	38 lm/W
CCT	3400 K
CRI	54

LOR	77%
Total flux	5247 lm
Total power	137 W



1 x High pressure mercury vapour lam	
Nominal lamp power	80 W
Lamp flux	4000 lm
Luminous efficacy	35 lm/W
CCT	3400 K
CRI	54

LOR 77°	%
Total flux 3087 Ir	m
Total power 89 V	W

Mounting mode

Wall mounted

Shape and measurements

Height: 20.08 in Diameter: 20.08 in Electric

System power: 89-137 W

Protection

IP: 55