

Product data sheet


RICHARD V (W. SHIELD ON SIDE FACING BUILDING)
9.889.2152.20
LEIPZIGER LEUCHTEN



IP
55


Mounting height approx. 4.00 m - 5.00 m, for medium light requirements. - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - Large aluminium reflector, inside finished in special white paint for max. light reflection - Aluminium cover, painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components are arranged on a block - Connection with adapter jack -Available in any RAL or DB colour without surcharge -Order pole, dia. 76 mm, separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure sodium vapour lamp

| | | | |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 50 W | LOR | 48% |
| Lamp flux | 3500 lm | ULOR | 11% |
| Luminous efficacy | 27 lm/W | Total flux | 1669 lm |
| CCT | 2000 K | Total power | 62 W |
| CRI | 25 | | |



1 x High pressure sodium vapour lamp

| | | | |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 70 W | LOR | 48% |
| Lamp flux | 5600 lm | ULOR | 11% |
| Luminous efficacy | 32 lm/W | Total flux | 2671 lm |
| CCT | 2000 K | Total power | 83 W |
| CRI | 25 | | |

Mounting mode

Pole top mounted

Shape and measurements

Height: 24.21 in
Diameter: 9.84 in

Electric

System power: 62-83 W

Protection

IP: 55