



# Product data sheet

CLARA LED  
9812422  
FLOS



- Outdoor luminaire for installation overdoor or on wall.
- Configuration: die-cast aluminium structure . EN AB-47100 alloy (low copper content).
- Double layer coating for high resistance to corrosion: The low copper Aluminium alloy is painted with a double coat using powders which are complaint with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents).The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting.
- Tempered sandblasted glass with silk-screen border. A robotic gluing system (silicone) fixes the glass to the structure.

## Light output 1 (integrated)



Lamp type	LED	CCT	6000 K
Nominal lamp power	18 W	CRI	75
Total flux	301 lm	LOR	100%
Luminous efficacy	17 lm/W	ULOR	50%
		Total power	18 W

## Mounting mode

Wall mounted

## Shape and measurements

Length: 18.11 in  
Width: 3.94 in  
Height: 4.17 in

## Adjustability

Fixed

## Electric

System power: 18 W  
Appliance Class: I

## Protection

IP: 65  
IK: 07