

# Product data sheet


RICHARD BII (FLOWER BED FITTING)  
9.880.5497.05  
LEIPZIGER LEUCHTEN



IP  
55

Decorative luminaire for lanes, driveways, terraces, gardens, and for night illumination and hazardous areas. - Impact-resistant clear/opal polycarbonate cylinder, UV-stabilized - Mirror lamellae for Richard BII made of burnished, anodized highest-grade aluminium - Reflector made of impact-resistant RESIST plexiglass, inside finished in white paint, outside painted in colour - Unit carrier made of corrosion-resistant cast aluminium, painted - Upright tube made of special steel, painted - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



1 x Compact fluorescent lamp			
Nominal lamp power	26 W	LOR	35%
Lamp flux	1800 lm	ULOR	11%
Luminous efficacy	23 lm/W	Total flux	636 lm
CCT	2899 K	Total power	28 W
CRI	90		

## Mounting mode

Standing / Bollard

## Shape and measurements

Height: 11.42 in  
Diameter: 7.09 in

## Electric

System power: 28 W

## Protection

IP: 55