

Product data sheet

LUCAS X (1-ARMED)
9.850.3142.15
LEIPZIGER LEUCHTEN



IP
55

Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge - Pole for single-bracket luminaire: dia. 76 mm, please order separately inquire separately for pole to suit double-bracket luminaire Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp

Nominal lamp power	50 W
Lamp flux	2000 lm
Luminous efficacy	28 lm/W
CCT	3400 K
CRI	54

LOR	84%
Total flux	1675 lm
Total power	59 W



1 x High pressure mercury vapour lamp

Nominal lamp power	80 W
Lamp flux	4000 lm
Luminous efficacy	38 lm/W
CCT	3400 K
CRI	54

LOR	84%
Total flux	3351 lm
Total power	89 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 19.69 in

Diameter: 22.44 in

Electric

System power: 59-89 W

Protection

IP: 55