


Product data sheet

COMPASS BOX
03.2600/QR-CBC51/50W/10°/24°/38°/60°
FLOS




Wall and ceiling luminaires 1,2 or 4 adjustable lights. Low voltage halogen, metal halide lamps or fluorescent lamps. Pressed steel, black painted optical body and extruded-aluminium outer structure with fixing system. Electrical connection and control devices incorporated in the luminaire.

Light output 1




1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gx5.3
Lamp flux	857 lm	LOR	100%
Luminous efficacy	17 lm/W	Total flux	857 lm
CCT	3000 K	Total power	50 W
CRI	99		




1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gx5.3
Lamp flux	1054 lm	LOR	100%
Luminous efficacy	21 lm/W	Total flux	1054 lm
CCT	3000 K	Total power	50 W
CRI	99		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gu5.3
Lamp flux	1182 lm	LOR	101%
Luminous efficacy	24 lm/W	Total flux	1189 lm
CCT	3000 K	Total power	50 W
CRI	100		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gx5.3
Lamp flux	856 lm	LOR	100%
Luminous efficacy	17 lm/W	Total flux	857 lm
CCT	3000 K	Total power	50 W
CRI	99		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 3.94 in

Width: 3.86 in

Height: 6.30 in

Adjustability

Free

Electric

System power: 50 W

Appliance Class: 0

Protection

IP: 20