


Product data sheet

NORA I (W. SHIELD ON SIDE FACING BUILDING CLEAR ATTACHMENT)
9.771.5547.35
LEIPZIGER LEUCHTEN



For medium light requirements, mounting height 3.50 - 4.00 m. - Impact-resistant clear or beaded polycarbonate attachment, UV-stabilized - Special reflector of premium highest-grade aluminium, burnished and anodized, for excellent illumination and glare protection -Aluminium luminaire body, inside finished in white paint, outside painted in colour - Aluminium unit carrier, painted white - Adapter jack connection - Available in any RAL or DB colour without surcharge - Scope of delivery includes special steel post/wall-mounted bracket, painted Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x Compact fluorescent lamp

Nominal lamp power	42 W	LOR	85%
Lamp flux	3200 lm	Total flux	2731 lm
Luminous efficacy	59 lm/W	Total power	46 W
CCT	2899 K		
CRI	90		

Mounting mode

Pole top mounted

Shape and measurements

Length: 24.21 in
Width: 12.20 in
Height: 6.50 in

Electric

System power: 46 W
Ballast: ECG
Appliance Class: I

Protection

IP: 55
Designation labels: CE

Other operating numbers

Ambient temperature range: -40...104°F