
Product data sheet

LUCAS IX (1-ARMED) 9.859.2072.15

LEIPZIGER LEUCHTEN








Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge - Pole for single-bracket luminaire: dia. 76 mm, please order separately inquire separately for pole to suit double-bracket luminaire Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



i x migri pressure socium vap	oui iairip
Nominal lamp power	150 W
Lamp flux	17000 lm

1 v Ligh proceure codium vapour lamp

Luminous efficacy 77 lm/W CCT 2000 K CRI 25

LOR ULOR

80%

4%

Total flux 13541 lm
Total power 176 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 23.62 in Diameter: 22.44 in

Electric

System power: 176 W

Protection

IP: 55