


Product data sheet

FL ROUND 333 PL MP S/A 26W 830 WH-RAL9016
8333261263310
PERFORMANCE IN LIGHTING



Suspended round LED luminaire for indoors, consisting of: Housing made from sheet steel and diecast aluminium, powder-coated / The fitting is available with different light optics: Micro-prismatic diffuser for efficient light diffusion, glare reduction and a high uniformity / Opal white diffuser cover for optimum light diffusion and excellent uniformity / LED Sidelight-Technology and light orienting plastic optic for a homogenous light distribution over the entire area of the cover / Light distribution direct or predominantly direct / Glare prevention in accordance with DIN EN 12464-1 (for designs with micro prism) / Colour rendering index Ra > 80 / Colour tolerance according to MacAdam ≤ 3 SDCM / Dimmable via TouchDIM / Complete with steel suspension cable (1.5 m), transparent power cord and ceiling rose / Complete with electric converter

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	26 W	CRI	80
Total flux	2882 lm	LOR	100%
Luminous efficacy	111 lm/W	Total power	26 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.59 in

Diameter: 13.07 in

Design

Color of housing: White

Electric

System power: 26 W

Appliance Class: I

Protection

IP: 20

IK: 07