


# Product data sheet

MIC 8 STANDING MOUNTED FLOODLIGHTS  
MI-50451-W-W40  
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Life time L90B10 Ta 25° 200,000, 300,000 - Life time L80B10 Ta 50° 490,000, > 500,000 - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Integral control gear installed in the spigot cover

## Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	28.8 W	CRI	80
Total flux	2926 lm	LOR	100%
Luminous efficacy	102 lm/W	Total power	28.8 W

## Mounting mode

Standing / Bollard, Wall mounted

## Shape and measurements

Height: 30.20 in  
Diameter: 7.76 in  
Weight: 4.9 kg

## Adjustability

Free

## Design

Color of housing: Black, White, Silver gray

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 28.8 W  
Voltage: 230 V AC  
Ballast: ECG  
Controller: Dimmable 1..10V, DALI  
Appliance Class: I

## Protection

IP: 65  
IK: 07  
Surface temperature: 40°C