



Product data sheet

FLEX STRIP 400 HE+ MONO - SWW
L64926HL
PROLED (MBN GMBH)



The PROLED FLEX STRIPS are perfect for indirect lightning, as custom made versions for fair or shop applications as well as for all kinds of illumination. Due to their shallow design and the individually adaptable lengths the PROLED FLEX STRIPS offer a wide spectrum of application possibilities. - High efficiency (110 - 130 Lumen per Watt) - High flexibility - adaptable to round shapes. - Installation with 3M adhesive tape on the strip's backside (self adhesive) - dimmable and controllable via DMX 512, DALI, KNX, 1-10V, CASAMBI, RF by MULTI power supplies/controller

Light output 1 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	14.4 W	CRI	90
Total flux	1700 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	14.4 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 39.37 in

Width: 0.39 in

Height: 0.08 in

Adjustability

Fixed

Electric

System power: 14.4 W

Controller: Dimmable 1..10V, DMX, DALI

Appliance Class: III

Protection

IP: 20

Other operating numbers

Ambient temperature range: 14...113°F