


Product data sheet

MINI AYERS TWO OPENING
9102-0-2-503-XX
UNILAMP



AYERS ground washer luminaires provide the users a low glare multi option light distribution. AYERS are able to withstand drive over applications at low speeds due to its robust manufacturing high strength aluminium cover and GFR polymer recess housing. It offers a high quality glass optical system giving high output in a low level fixture. Reflectors built from Photopia engineering software plus the high lumen output COB LED from renowned manufacturers allow AYERS a high intensity sharp light output. It is a perfect choice to illuminate ground surfaces. AYERS is supplied with a post-cured silicone gasket and pre-wired IP68 anti-condensation kit. spec • Designed, Manufactured and tested according to IEC 60598-1, IEC 60598-2-1, IEC 60598-2-13 and VDE regulations. • LM6 Die Cast Aluminium, High strength Cast Aluminium and Extruded Aluminium body. • GFR Polymer recess housing. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Safety pressed glass cover. • Polycarbonate cover (Mini AYERS). • Post-cured silicone gasket. • High quality LED module and driver. • High quality AC COB module (Mini AYERS). • GFR PA6.6 Terminal block. • M16(Mini AYERS) and M20 cable gland. • Pre-wired with outdoor cable. • Installation work has to be carried on according to the enclosed product manual. • The water drainage system must be tested to ensure that it is working sufficiency and efficiency.

Light output 1



1 x LED			
Nominal lamp power	8.2 W	LOR	5%
Lamp flux	1290 lm	ULOR	4%
Luminous efficacy	157 lm/W	Total flux	65 lm
CCT	2700 K	Total power	8.2 W
CRI	80		

Mounting mode

Floor recessed

Shape and measurements

Length: 4.36 in
Width: 4.35 in
Height: 7.45 in

Adjustability

Fixed

Electric

System power: 8.2 W
Appliance Class: III

Protection

IP: 67
IK: 10