## Product data sheet

AZUR POST LED 4K CLO ND2 300331-465

FAGERHULT







Installation Luminaire for assembly on a post, with post top Ø 60 mm or Ø 76 mm. Connection Supplied with 5 m cable 2x1.5 mm². Design Body of cast aluminium and stainless steel details. Shade of UV-stabilised, clear polycarbonate. Re-lamping from the top. Driver in the luminaire and fuse insert integrated in the post. Louvre Acrylic louvre. Reflector Reflector of anodised aluminium. Standard colour Anthracite grey (Gris 900 Sablé). Luminaires with DALI as standard can be ordered in Alu-grey (RAL 9006) with additional suffix code -236.

## Light output 1 (integrated)



| Lamp type          | LED     | CCT         | 4000 K |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 16 W    | CRI         | 80     |
| Total flux         | 945 lm  | LOR         | 100%   |
| Luminous efficacy  | 59 lm/W | ULOR        | 6%     |
|                    |         | Total power | 16 W   |

Mounting mode

Pole top mounted

Shape and measurements

Height: 15.75 in Diameter: 22.72 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 16 W

Protection

IP: 65