# Product data sheet

MARTINI 32 STREET AND AREA LIGHTING LUMINAIRES MN-91262-M-W40

LIGMAN












- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Formed sheet aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Surge protection 10 kV

## Light output 1 (integrated)



Lamp type
Nominal lamp power
Total flux
Luminous efficacy

LED	CCT
53.5 W	CRI
6565 lm	LOR
123 lm/W	Total power

4032 k
80
100%
53.5 W

#### Mounting mode

Wall mounted, Pole top mounted

#### Shape and measurements

Length: 28.74 in Width: 12.68 in Height: 3.54 in Weight: 13 kg

## Adjustability

Fixed

#### Design

Color of housing: Black, White, Silver gray

## Glare protection

Glare protection: UGR < 19

#### Electric

System power: 53.5 W Voltage: 230 V AC Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

## Protection

IP: 54 IK: 07

Surface temperature: 40°C